

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical  
Panels with ClimaPlus™ Performance/  
USG Donn® Brand Finline® DXF™  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

Fine-Textured Panel

## FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- USDA Certified Biobased Product.<sup>7</sup>
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Offices
- Classrooms
- Reception/lobby areas
- Hotels
- Conference areas
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
 USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
 fax: 888 874-2348 | [usg.com](http://usg.com)  
 CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
 TECHNICAL INFORMATION  
 AND LEED REPORT TOOL  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)

TECHNICAL SERVICES  
 800 USG.4YOU (874-4968)



PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 ULCOM/GG  
 UL 2818

30 YEAR LIMITED SYSTEM  
 WARRANTY  
 • No Visible Sag  
 • Mold/Mildew Protection

10 YEAR  
 AVAILABILITY  
 4211, 4221, 4231,  
 4411, 4421, 4742,  
 4744

HRC HIGH RECYCLED  
 CONTENT



## USG OLYMPIA™ MICRO™ PANELS UNPERFORATED

## USG OLYMPIA™ MICRO™ PANELS 50 NRC<sup>6</sup>

## USG OLYMPIA™ MICRO™ PANELS 60 NRC<sup>6</sup>

## USG OLYMPIA™ MICRO™ ILLUSION™ TWO/24 PANELS

### PATTERNS

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
				NRC	CAC Min.	LR <sup>2</sup>						
SQ	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low	[Green Arrow]	44%	\$\$
	2'x4'x5/8"		4913	—	35	0.86						
SQ	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low	[Green Arrow]	44%	\$\$
	2'x4'x5/8"		4411	0.50	30	0.86						
	2'x4'x5/8"		4411HRC	0.50	30	0.86						
SLT	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low	[Green Arrow]	44%	\$\$
	2'x2'x5/8"		4221HRC	0.50	35	0.86						
	2'x4'x5/8"		4421	0.50	35	0.86						
FLB	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low	[Green Arrow]	44%	\$\$
	2'x2'x5/8"		4231HRC	0.50	35	0.86						
	2'x4'x5/8"		4431	0.50	35	0.86						
SQ	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low	[Green Arrow]	61%	\$\$
	2'x4'x3/4"		4751	0.60	33	0.86						
SLT	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low	[Green Arrow]	61%	\$\$
	2'x4'x3/4"		4753	0.60	35	0.86						
FLB	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low	[Green Arrow]	61%	\$\$
	2'x4'x3/4"		4755	0.60	35	0.86						
SLT <sup>4</sup>	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low	[Green Arrow]	61%	\$\$
ILT <sup>5</sup>	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I,J	Low	[Green Arrow]	61%	\$\$

### USG Illusion™ Two/24



The look of 2'x2' panels

### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on [usg.com](http://usg.com) and at [productguide.ulenvironment.com](http://productguide.ulenvironment.com).

### ClimaPlus™ Warranty Performance<sup>3</sup>

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

### GRID PROFILE OPTIONS

A USG DX™/DXL™	B USG DXW™	C <sup>7</sup> USG Centricitee™ DXT™	D USG DX™/DXL™	E USG Centricitee™ DXT™	F USG Identitee® DXI™	G USG Fineline® DXF™	H USG Fineline® 1/8 DXFF™	I USG Centricitee™ DXT™	J USG Identitee® DXI™

### PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC2180

**ASTM E1264 classification**  
 Type III, Form 2, Pattern CE

**ASTM E84 and CAN/ULC S102  
 surface-burning characteristics**  
 Class A

Flame spread: 25 or less  
 Smoke developed: 50 or less

**Online tools**  
[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

**Weight**  
 0.78-1.03 lb./sq. ft.

**Thermal resistance**  
 R-1.4 (5/8" panels)  
 R-1.7 (3/4" panels)

**Maximum backloading**  
 See USG 30-Year Limited System  
 Warranty Commercial Applications  
 (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft  
 brush or vacuum.

### Notes

- For details, see LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com).
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102) and ClimaPlus™ Ceilings Certification of Performance (SC2451).
- Panels have 15/16" routing.
- Panels have 9/16" routing.

6. Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.

7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on [biopreferred.gov](http://biopreferred.gov) website.

**Notice**  
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 11-16  
 © 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by  
 USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXL, DXL, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

